



rev	date	engineer	remarks
-	-	-	-
-	-	-	-
-	-	-	-

THIS DOCUMENT IS SUBJECT OF THE TECHNICAL PRODUCT MANAGEMENT SYSTEM. ANY REVISIONS OR CHANGES TO THIS DOCUMENT SHALL BE APPROVED BY BROSHUIS BV. THEREBY IS NOT PERMITTED TO REPRODUCE OR TRANSMIT IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF BROSHUIS BV.

Dolly	Innerbeam	Centerbeam	Suspension	BROSHUIS/independent	Side rave	(F) U 160 cl. (R) U240 cl.
Extensions	Extensions	Extensions	Axles	BROSHUIS/independent	Stake pockets	96x66x6
500	500	500	Raise/lower	+290/-70	Deck	28mm & 8/10 checkpl.
1150	800	800	Tyres	245/70R17.5	Weldings	K-13320
	1200	1200	Fifth wheel load	30.000 (kg)	Drain holes	Ø13
	2000	2000	Bogie load	24.000(kg) + 60.000(kg) technical	Type vehicle	2-5ABSD-SL2/2
	2500	2500			Chassis number	
	3000	3000	Client	Westdijk		
	3500	3500	Gen. Tol. ISO 13920 AE, ISO 1101			
	4000	4000	Roughness ISO 1302, Welding K-13320		Break sharp edges: $\sqrt{0.5}$ AS	
	4500	4500	drawn by: Gerben Diender	Third angle	mass: 78823.2 kg. (for information purpose only)	
	5000	5000	date: 21-Feb-17		ID:	
	5500	5500	preceded: 160115		Title:	1701040.ASM
	6350	6350			units: mm	2-5ABSD-SL2/2
					scale: 1:50	
					sheet: 1-1	
					A1	
					state	revision
					In Work	article Number
						A 1701040_U1TGESCHOVEN



www.broshuis.com